



## VOLANTE COLLECTION

*inspired by Scandi Design*

NORDIKKA | TROMSO | BODO





Boathouse Oak



Cashew



Brushed Elm



Driftwood



Dusty Oak



Shale Oak



Mountain Ash



Smoked Oak



Vintage Oak

# Three ranges in LVT & SPC

Nordikka is our wood plank collection. It is available in a 2.5mm LVT for direct adhesion to the sub floor, and a 4mm SPC rigid core option for clicked and floated fitting.

There are ten colour / design options.

Tromso & Bodo are our herringbone collections. Tromso is a 2.5mm LVT for direct adhesion to the sub floor, and Bodo is a 5mm SPC rigid core option for clicked and floated fitting.

There are nine colour design options

## new arrivals.....

We have just launched another 11 colours that share the same colour range across plank and herringbone for multi dimensional design layouts.

Willow Bark



Next day service to our trade customers  
Substantial stocks ready for your project.

# Tromso & Bodo Herringbone



light washed oak



slate grey



white maple



woodland fir



limed oak



smoked ash



aged walnut



honey oak



norweigen oak

# at home at work performance .....

COMMERCIAL GRADE FLOORING



# our new colours and designs.

Matching colours across the herringbone and plank formats.



forest oak



birchwood



honey elm



cedar



grey ash



highland walnut



rustic grey



reclaimed fir



siberian spruce



rustic oak



white ash



Installed in three different ways  
Traditional | Chevronesque | Duo

# Nordikka Plank | Commercial LVT

## TEST PARAMETER



| CHARACTERISTICS                      | TEST METHOD    | RESULT                           |
|--------------------------------------|----------------|----------------------------------|
| Dimension                            | EN 427         | 185x1229mm                       |
| Thickness-Overall                    | EN 428         | 2.5mm                            |
| Thickness-Wear Layer                 | EN 429         | 0.55mm                           |
| Total Weight                         | EN 430         | 4.90kg/m <sup>2</sup>            |
| Caster Wheel Chair                   | EN 425         | Pass                             |
| Abrasion Resistance                  | EN 660-2       | T grade                          |
| Indentation Residual                 | EN 433         | Pass                             |
| Colour Fastness                      | EN ISO 105-BO2 | ≥6                               |
| Fire Rating                          | EN13501-1      | B <sub>fl</sub> -s1              |
| Effects of Stain                     | EN 423         | Pass                             |
| Residual Indentation after Stability | EN 434         | Shrinkage≤0.08%<br>Curling≤2.0mm |
| Peeling Strength of Layers           | EN 431         | Pass                             |
| Flexibility-10mm Mandrel             | EN 435         | No Damage                        |
| Resistance to Chemicals              | EN 423         | Class 0                          |
| Toxic                                | EN 71Part3     | Pass                             |
| Slip Resistance                      | DIN 13893      | R10                              |
| Performance Classification           | EN 685         | 23/34/43                         |
| GB/T 4085 GB 86t24 B1                |                | Pass                             |
| CNS 8907                             |                | Pass                             |

Suitable for use with underfloor heating up to 27°C

Wear guarantee:  
Lifetime Residential  
15 Years Commercial



# Nordikka Plank | Commercial SPC

## TEST PARAMETER



| CHARACTERISTICS                      | TEST METHOD    | RESULT                           |
|--------------------------------------|----------------|----------------------------------|
| Dimension                            | EN 427         | 183X1220mm                       |
| Thickness-Overall                    | EN 428         | 4.0mm                            |
| Thickness-Wear Layer                 | EN 429         | 0.5mm                            |
| Total Weight                         | EN 430         | 8.00kg/m <sup>2</sup>            |
| Caster Wheel Chair                   | EN 425         | Pass                             |
| Abrasion Resistance                  | EN 660-2       | T grade                          |
| Indentation Residual                 | EN 433         | Pass                             |
| Colour Fastness                      | EN ISO 105-BO2 | ≥6                               |
| Impact Sound Reduction               | EN ISO 10140-3 | 19dB                             |
| Fire Rating                          | EN13501-1      | B <sub>f</sub> -s1               |
| Effects of Stain                     | EN 423         | Pass                             |
| Residual Indentation after Stability | EN 434         | Shrinkage≤0.08%<br>Curling≤2.0mm |
| Peeling Strength of Layers           | EN 431         | Pass                             |
| Flexibility-10mm Mandrel             | EN 435         | No Damage                        |
| Resistance to Chemicals              | EN 423         | Class 0                          |
| Toxic                                | EN 71Part3     | Pass                             |
| Slip Resistance                      | DIN 13893      | R10                              |
| Performance Classification           | EN 685         | 23/34/43                         |
| GB/T 4085 GB 86t24 B1                |                | Pass                             |
| CNS 8907                             |                | Pass                             |

Suitable for use with underfloor heating up to 27°C

Wear guarantee:

Lifetime Residential

15 Years Commercial



# Tromso Herringbone | Commercial LVT

## TEST PARAMETER

**Tromso®**  
— HERRINGBONE LVT —

| CHARACTERISTICS                      | TEST METHOD    | RESULT                               |
|--------------------------------------|----------------|--------------------------------------|
| Dimension                            | EN 427         | 118x590mm                            |
| Thickness-Overall                    | EN 428         | 2.5mm                                |
| Thickness-Wear Layer                 | EN 429         | 0.55mm                               |
| Total Weight                         | EN 430         | 4.90kg/m²                            |
| Caster Wheel Chair                   | EN 425         | Pass                                 |
| Abrasion Resistance                  | EN 660-2       | T grade                              |
| Indentation Residual                 | EN 433         | Pass                                 |
| Colour Fastness                      | EN ISO 105-BO2 | ≥6                                   |
| Fire Rating                          | EN13501-1      | B <sub>fl</sub> -s1                  |
| Effects of Stain                     | EN 423         | Pass                                 |
| Residual Indentation after Stability | EN 434         | Shrinkage ≤ 0.08%<br>Curling ≤ 2.0mm |
| Peeling Strength of Layers           | EN 431         | Pass                                 |
| Flexibility-10mm Mandrel             | EN 435         | No Damage                            |
| Resistance to Chemicals              | EN 423         | Class 0                              |
| Toxic                                | EN 71Part3     | Pass                                 |
| Slip Resistance                      | DIN 13893      | R10                                  |
| Performance Classification           | EN 685         | 23/34/43                             |
| GB/T 4085 GB 86t24 B1                |                | Pass                                 |
| CNS 8907                             |                | Pass                                 |

Suitable for use with underfloor heating up to 27°C

Wear guarantee:  
Lifetime Residential  
15 Years Commercial



# Bodo Herringbone | Commercial LVT

## TEST PARAMETER



| CHARACTERISTICS                      | TEST METHOD    | RESULT                           |
|--------------------------------------|----------------|----------------------------------|
| Dimension                            | EN 427         | 118x590mm                        |
| Thickness-Overall                    | EN 428         | 5.0mm                            |
| Thickness-Wear Layer                 | EN 429         | 0.5mm                            |
| Total Weight                         | EN 430         | 10.00kg/m <sup>2</sup>           |
| Caster Wheel Chair                   | EN 425         | Pass                             |
| Abrasion Resistance                  | EN 660-2       | T grade                          |
| Indentation Residual                 | EN 433         | Pass                             |
| Colour Fastness                      | EN ISO 105-BO2 | ≥6                               |
| Impact Sound Reduction               | EN ISO 10140-3 | 19dB                             |
| Fire Rating                          | EN13501-1      | B <sub>fl</sub> -s1              |
| Effects of Stain                     | EN 423         | Pass                             |
| Residual Indentation after Stability | EN 434         | Shrinkage≤0.08%<br>Curling≤2.0mm |
| Peeling Strength of Layers           | EN 431         | Pass                             |
| Flexibility-10mm Mandrel             | EN 435         | No Damage                        |
| Resistance to Chemicals              | EN 423         | Class 0                          |
| Toxic                                | EN 71Part3     | Pass                             |
| Slip Resistance                      | DIN 13893      | R10                              |
| Performance Classification           | EN 685         | 23/34/43                         |
| GB/T 4085 GB 86t24 B1                |                | Pass                             |
| CNS 8907                             |                | Pass                             |

Suitable for use with underfloor heating up to 27°C

Wear guarantee:  
Lifetime Residential  
15 Years Commercial





**easy  
clean  
robust ...**

LVT & SPC FROM VOLANTE





CALL 020 8947 6561

50 Cox Lane | Chessington | KT9 1TW

[www.volante.uk.net](http://www.volante.uk.net)



Just one of the extensive product collections from  
Volante your trade partner for flooring.